



FARMTRAC

FARMTRAC 6050E

Simple, Versatile, Easy-to-Use Machine.

The 6050E comes with proven engineering, offering smooth operation and solid power for general-purpose farming.

Model Name			FARMTRAC 6050E
Drive System			4WD
Engine	Model		E4.276 TC CRDi
	Manufacturer		Escorts Kubota Ltd.
	Cylinder	n°	3
	Power at rated engine speed (ECE R120)	Hp/Kw	49/36.5
	Max. power (ECE R120)	Hp/Kw	49/36.5
	Displacement	cc	2760
	Max. engine speed (rated)	rpm	2000
	Emissions		Stage V
	Aspiration		TC CRDi
	Fuel tank capacity	litre	60
	Air cleaner		DRY type with Clogging sensor
Transmission	Gear		8F + 8R
	Type		Partial Synchro (F/R Synchro)
Rear Axle	Type		Epicyclic Planetary Reduction
	Differential Lock		Std
Clutch	Type		Double Clutch - Independent lever for PTO Clutch
Brake type			Oil Immersed Brake
Trailer Brake			Opt.
Speed @ Rated ERPM	Forward - Max./Min	km/h	Max. 29.9 / Min. 2.6
	Reverse - Max./Min	km/h	Max. 29.8 / Min. 2.6
Max speed		km/h	32.5@2180
PTO	Speed (rpm)		540 @ 1728 540E @ 1251
	Type		Independent
3-Point hitch			CAT I
Steering	Type		Power Steering
	Pump Capacity	l/min	19.8
Hydraulics	Control system		Position & Draft control
	Lift Capacity - at lower link end	kg	1500
	Hydraulic pump Capacity	l/min	32.4
	Standard auxiliary valve		2DE/2SE
Tyre	Front standard tyre		280/70R16
	Rear standard tyre		360/70R28
Dimensions	Overall length	mm	3415w/o Front Ballast
	Overall width	mm	1830
	Overall height	mm	2630 (Up to Beacon lamp)
	Wheel base	mm	1885
	Ground clearance	mm	400
	Front track width	mm	1425
	Rear track width	mm	1448
	Turning radius w/o brake	m	3.2±0.1
	Tractor weight	kg	2245
Weight	Maximum permissible front weight	kg	1200
	Maximum permissible rear weight	kg	2300
	Maximum permissible total weight	kg	3500

FARMTRAC

KUBOTA (Deutschland) GmbH, Senefelderstraße 3-5, 63110 Rodgau

Website: www.farmtrac-eu.com

