

FARMTRAC

FARMTRAC 6075E

Built for Real Work and Real Results.

Designed for demanding field conditions, the 6075E blends high lifting capacity, engine efficiency and rugged durability in one reliable machine.



Model Name			FARMTRAC 6075E
Drive System			4WD
Engine	Model		E4.368 TC
	Manufacturer		Escorts Kubota Ltd.
	Cylinder	n°	4
	Power at rated engine speed (ECE R120)	Hp/Kw	74/54.4
	Max. power (ECE R120)	Hp/Kw	74/54.4
	Displacement	cc	3680
	Max. engine speed (rated)	rpm	2000
	Emissions		Stage V
	Aspiration		TCI-ECRT
	Fuel tank capacity	litre	100
	Air cleaner		DRY type with Clogging sensor
Transmission	Gear		24F + 24R - Creeper
	Type		Synchromesh
Rear Axle	Type		Epicyclic Planetary Reduction
	Differential Lock		Std
Clutch	Type		Double Clutch - Independent lever for PTO Clutch
Brake type			Oil Immersed Brake
Trailer Brake			Dual hydraulic or Pneumatic (Opt.)
Speed @ Rated ERPM	Forward - Max./Min	km/h	Max. 33.44 / Min. 0.46
	Reverse - Max./Min	km/h	Max. 28.36 / Min. 0.39
Max speed @ fly up			36.44@2180
PTO	Speed (rpm)		540 @ 1938 1000 @ 1962
	Type		Independent
	Ground Speed PTO/ MRPTO		GPTO
3-Point hitch			CAT 2
Steering	Type		Power Steering
	Pump Capacity	l/min	20
Hydraulics	Control system		Position & Draft control
	Lift Capacity - at lower link end	kg	3000
	Hydraulic pump Capacity	l/min	50.4
	Standard auxiliary valve		3xDE / 3xSE
Tyre	Front standard tyre		280/85 R24
	Rear standard tyre		420/85 R30
Dimensions	Overall length	mm	4144
	Overall width	mm	2023
	Overall height	mm	2900
	Wheel base	mm	2300
	Ground clearance	mm	385
	Front track width	mm	1666
	Rear track width	mm	1592
	Turning radius w/o brake	m	4.8±0.1
	Tractor weight	kg	3855
Weight	Maximum permissible front weight	kg	2205
	Maximum permissible rear weight	kg	3650
	Maximum permissible total weight	kg	5855

FARMTRAC

KUBOTA (Deutschland) GmbH, Senefelderstraße 3-5, 63110 Rodgau

Website: www.farmtrac-eu.com

