



FARMTRAC

FARMTRAC 6075EN

Power where space is tight

From narrow orchards to specialised tasks, the 6075EN delivers compact strength, agility and precision for modern farmers working in tight spaces.

Model Name			FARMTRAC 6075EN
Drive System			4WD
Engine	Model		E4.368 TC
	Manufacturer		Escorts Kubota Ltd.
	Cylinder	n°	4
	Power at rated engine speed (ECE R120)	Hp/Kw	74/54.4
	Max. power (ECE R120)	Hp/Kw	74/54.4
	Displacement	cc	3680
	Max. engine speed (rated)	rpm	2000
	Emissions		Stage V
	Aspiration		TCI-ECRT
	Fuel tank capacity	litre	70
	Air cleaner		DRY type with Clogging sensor
Transmission	Gear		24F + 24R - Creeper
	Type		Synchromesh
Rear Axle	Type		Epicyclic Planetary Reduction
	Differential Lock		Std
Clutch	Type		Double Clutch - Independent lever for PTO Clutch
Brake type			Oil Immersed Brake
Trailer Brake			Dual hydraulic (Opt.)
Speed @ Rated ERPM	Forward - Max./Min	km/h	Max. 33.38 / Min. 0.46
	Reverse - Max./Min	km/h	Max. 24.84 / Min. 0.34
Max speed		km/h	36.38@2180
PTO	Speed (rpm)		540 @ 1938 540E @ 1648
	Type		Independent
	Ground Speed PTO/ MRPTO		GPTO
3-Point hitch			CAT 2
Steering	Type		Power Steering
	Pump Capacity	l/min	19.8
Hydraulics	Control system		Position & Draft control
	Lift Capacity - at lower link end	kg	2500
	Hydraulic pump Capacity	l/min	50
	Standard auxiliary valve		3xDE/ 3xSE - with detent/float
Tyre	Front standard tyre		280/70 R16 - Radial
	Rear standard tyre		380/70 R24 - Radial
Dimensions	Overall length	mm	3577 (w/o front ballast)
	Overall width	mm	1480
	Overall height	mm	2493
	Wheel base	mm	2157
	Ground clearance	mm	338
	Front track width	mm	1145
	Rear track width	mm	981
	Turning radius w/o brake	m	3.7±0.1
	Tractor weight	kg	3150
Weight	Maximum permissible front weight	kg	1815
	Maximum permissible rear weight	kg	2880
	Maximum permissible total weight	kg	4695

FARMTRAC

KUBOTA (Deutschland) GmbH, Senefelderstraße 3-5, 63110 Rodgau

Website: www.farmtrac-eu.com

